



Welcome to
Chery International

[Home](#) [Chery Vehicles](#) [About Chery](#) [Chery Global](#)

 [Search](#)

Chery QQ3

[Exterior](#) [Interior](#) [Safety & Security](#) [Specifications](#) [Gallery](#)

[Exterior](#)
[Interior](#)
[safety & security](#)
[Specifications](#)
[Gallery](#)

Star Models

[A1](#) [A5](#) [Cowin](#) [Tiggo](#)

[EaStar Cross](#)

All Models

[A1](#) [A3](#) [A5](#) [Cowin](#) [EaStar](#) [Karry](#)

[QQ3](#) [QQ6](#) [Riich](#) [Tiggo](#)

[EaStar Cross](#)

Chery Club

[Wallpaper](#)

[Gallery](#)

[Registration](#)

[Send to Friends](#)

Chery Global

These specifications are subjected to change without notice. Please contact your Chery dealer/distributor for detailed specifications

Engine	0.8L		1.1L
Transmission	5MT	5AMT	5MT
Drive	FF		
Engine			
Engine code	SQR372	SQR472F	
Number of cylinders	4 in line		
Valve mechanism	12 valves DOHC	16 valves DOHC	
Fuel injection system	Electronic Multipoint Injection		
Displacement (cc)	812	1083	
Bore×stroke (mm)	72×66.5		
Compression ratio	9.5: 1		
Maximum power (Kw/rpm)	38/6000	50/6000	
Maximum torque (Nm/rpm)	70/3500~4000	90/3500~4000	
Fuel tank capacity (L)	38		
Fuel consumption at 90KM/h(Litres/100km)	6	5	6 5.2
Maximum speed (km/h)	130		
Fuel type	Unleaded Gasoline		
Dimensions & Weight			
Length×Width×Height (mm)	3550×1495×1485/1530(choose rack)		
Wheelbase (mm)	2340		
Front tread (mm)	1295		
Rear tread (mm)	1260		
Minimum ground clearance(full loading) (mm)	125	115	
Turning radius(minimum) (m)	5		
Kerb weight (kg)	880	900	890
Tyre Size	155/65R13 73H		
Suspension & Brake			
Front suspension	Independent Macpherson strut with cylindrical coil spring, single transverse link and dual-acting damper		
Rear suspension	Nonindependent trailing arm type with cylindrical coil spring and dual-acting tube damper		
Front Brake	Disc		
Rear Brake	Drum		
ABS+EBD	Optional		

[All Models](#)