



Welcome to
Chery International

[Home](#) [Chery Vehicles](#) [About Chery](#) [Chery Global](#)

 [Search](#)

Chery QQ6

[Exterior](#) [Interior](#) [Safety & Security](#) [Specifications](#) [Gallery](#)

[Exterior](#)
[Interior](#)
[safety & security](#)
[Specifications](#)
[Gallery](#)

Star Models

[A1](#) [A5](#) [Cowin](#) [Tiggo](#)

[EaStar Cross](#)

All Models

[A1](#) [A3](#) [A5](#) [Cowin](#) [EaStar](#) [Karry](#)

[QQ3](#) [QQ6](#) [Riich](#) [Tiggo](#)

[EaStar Cross](#)

Chery Club

[Wallpaper](#)

[Gallery](#)

[Registration](#)

[Send to Friends](#)

Chery Global

These specifications are subjected to change without notice. Please contact your Chery dealer/distributor for detailed specifications

Engine	1.3L	1.1L
Transmission	5MT	
Drive	FF	
Engine		
Engine code	SQR473F	SQR472F
Number of cylinders	4 in line	
Valve mechanism	16 valves DOHC	
Fuel injection system	Electronic Multipoint Injection	
Displacement (cc)	1297	1083
Bore×stroke (mm)	73×77.5	72/66.5
Compression ratio	10.01	9.5: 1
Maximum power (Kw/rpm)	61/6000	50/6000
Maximum torque (Nm/rpm)	114/3800~4500	90/3500~4000
Fuel tank capacity (L)	45	
Fuel consumption at 90KM/h(Litres/100km)	6.5	6.1
Maximum speed (km/h)	160	130
Fuel type	Unleaded Gasoline	
Dimensions & Weight		
Length×Width×Height (mm)	3995×1640×1520	
Wheelbase (mm)	2340	
Front tread (mm)	1420	
Rear tread (mm)	1420	
Minimum ground clearance(full loading) (mm)	130	
Turning radius(minimum) (m)	4.8	
Kerb weight (kg)	1050	990
Tyre Size	175/60R14 79H	
Suspension & Brake		
Front suspension	Independent Macpherson strut with coil spring, dual acting tube damper and single transverse link	
Rear suspension	Rigid axle suspension with trailing arm, cylindrical coil spring, dual-acting tube damper	
Front Brake	Disc	
Rear Brake	Drum	
ABS+EBD	Optional	

[All Models](#)