





**QQ6 Specifications**

	Powertrain	1.1-MT	1.3-MT
	Model code	SQR7110S21	SQR7130S21
<b>Emission</b>			
	EU II	●	●
<b>Safety &amp; security</b>			
Seat belt	Front 3-point seat belts with ELR	●	●
	Rear outer 3-point seat belts with ELR	●	●
Brake	Front discs brake	●	●
	Rear drum brake	●	●
Anti-theft	Energy-absorbing steering column	●	●
	Engine immobilizer		●
	Body anti-theft		●
	Four door jam alarm	●	●
Foglight	Dual tone horn	●	●
	Front foglights	●	●
	Rear foglights	●	●
	High mounted brakelamp	●	●
<b>Technical</b>			
	Overall length (mm)	3998	
	Overall width (mm)	1640	
	Overall height (mm)	1535	
	Wheelbase (mm)	2340	
	Turning radius(m)	4.8	
	Weights - curb weight / gross vehicle weight rating (kg)	990/1365	1050/1425
	The accelerate time for 0-100km/h(s)	20	17.8
	Max. speed (km/h)	130	164
	Engine code	SQR472	SQR473F
	Gearbox code	QR512	QR513
	Transmission - number of speeds / type	5MT	
	Maximum power (kw/rpm)	50/6000	61/6000
	Maximum torque (n.m/rpm)	90/3500-4000	114/3800-4500
	Engine - liters / (cc)	1083	1297
	Engine bore(mm)	72	73
	Engine stroke(mm)	66.5	77.5
	Engine configuration - number of cylinders	4 in line	
	Engine compression ratio	9.5:1	10:1
	Number of valves per cylinder	4	

Seating capacity	5
Number of doors	4
Driven wheels	Front
Fuel - type / other fuel type	Fuel
Fuel tank capacity (L)	45
Wheel	175/60 R14 tyre
Front suspension - type / stabilizer bar / spring type / wheel dependence	Macpherson strut with cylindrical coil spring, dual-tube damper and single transverse link
Rear suspension - type / stabilizer bar / spring type / wheel dependence	Rigid axle trailing arm type with cylindrical coil spring and dual-tube damper

 QQ6 Specifications  
[Download](#)

 QQ6 Specifications  
[Download](#)

[HOME](#) [SITEMAP](#) [CONTACT US](#) [CAREER](#) [LEGAL](#) [PRIVACY](#)

Select your language  English  Русский  Español  العربية

Select Family Site  Select Country :

Copyright © 2010 Chery Inc. All Rights Reserved