



Welcome to
Chery International

[Home](#) [Chery Vehicles](#) [About Chery](#) [Chery Global](#)

Search

Chery Riich

[Exterior](#) [Interior](#) [Safety & Security](#) [Specifications](#) [Gallery](#)

[Exterior](#)
[Interior](#)
[safety & security](#)
[Specifications](#)
[Gallery](#)

Star Models

[A1](#) [A5](#) [Cowin](#) [Tiggo](#)

[EaStar Cross](#)

All Models

[A1](#) [A3](#) [A5](#) [Cowin](#) [EaStar](#) [Karry](#)

[QQ3](#) [QQ6](#) [Riich](#) [Tiggo](#)

[EaStar Cross](#)

Chery Club

[Wallpaper](#)

[Gallery](#)

[Registration](#)

[Send to Friends](#)

Chery Global

These specifications are subjected to change without notice. Please contact your Chery dealer/distributor for detailed specifications

Engine	1.3L
Transmission	5MT
Drive	FF
Engine	
Engine code	SQR473F
Number of cylinders	4 in line
Valve mechanism	16 valves DOHC
Fuel injection system	Electronic Multipoint Injection
Displacement (cc)	1297
Bore×stroke (mm)	73×77.5
Compression ratio	10:01
Maximum power (Kw/rpm)	61/6000
Maximum torque (Nm/rpm)	114/3800~4500
Fuel tank capacity (L)	45
Fuel consumption at 90KM/h(Litres/100km)	7.7
Maximum speed (km/h)	140
Fuel type	Unleaded Gasoline
Dimensions & Weight	
Length×Width×Height (mm)	4040×1640×1900
Wheelbase (mm)	2625
Front tread (mm)	1420
Rear tread (mm)	1420
Minimum ground clearance(full loading) (m)	150
Turning radius(minimum) (m)	5.5
Kerb weight (kg)	1220
Tyre Size	165/70R14 85H
Suspension & Brake	
Front suspension	Independent Macpherson strut with coil spring, single transverse link and dual acting tube damper
Rear suspension	Rigid axle suspension with leaf spring ,dual-acting tube damper
Front Brake	Disc
Rear Brake	Drum
ABS+EBD	Optional

All Models