

<b>Chery V5 2008</b>	<b>Chery Automobile Source</b>
Engine	2.4L
Transmission	4MT
Drive	FF
<b>Engine</b>	
Engine code	4G64S4M
Number of cylinders	4 in line
Valve mechanism	16 valves SOHC
Fuel injection system	Electronic Multipoint Injection
Displacement (cc)	2350
Bore×stroke (mm)	86.5×100
Compression ratio	9:01
Maximum power (Kw/rpm)	95/5500
Maximum torque (Nm/rpm)	195/2500~3000
Fuel tank capacity (L)	62
Fuel consumption at 90KM/h(Litres/100km)	8.8
Maximum speed (km/h)	178
Fuel type	Unleaded Gasoline
<b>Dimensions &amp; Weight</b>	
Length×Width×Height (mm)	4662×1820×1590
Wheelbase (mm)	2800
Front tread (mm)	1550
Rear tread (mm)	1530
Minimum ground clearance(full loading) (mm)	125
Turning radius(minimum) (m)	6
Kerb weight (kg)	1505
Tyre Size	205/55R16 91W
<b>Suspension &amp; Brake</b>	
Front suspension	Independent Macpherson strut with coil spring, dual acting tube damper and anti-roll bar
Rear suspension	Independent multi-link with culindrical coil spring, dual-acting tube damper and anti-roll bar
Front Brake	Disc(venti)
Rear Brake	Disc
ABS+EBD	Yes