

ESCALADE ESV SPECIFICATIONS

Braking	
_	Authorit floor Anti-lade Building Contains to the state of four traditions
Brakes	4-wheel discs , Anti-lock Braking System, twin-piston front calipers
Suspension & Handling	
Road-Sensing Suspension	Coil-over-shock front/5-link rear with bi-modal mono-tube shocks and computer-controlled real-time damping (Standard with $18"$ wheels)
Magnetic Ride Control	Coil-over shock-front/5-link rear with magneto-rheologicial fluid-filled shocks and computer-controlled real-time damping (Standard with 22" wheels)*
StabiliTrak with Rollover Mitigation	Computer-controlled, 4-channel electronic stability control system with rollover mitigation
Construction	
Construction	All-welded fully boxed ladder-type frame
Fires & Wheels	
Tires	P265/65R18 blackwall touring tires (Standard)
	P285/45R22 blackwall performance touring tires (Included and only available on Ultra Luxury Collection and Platinum)**
Wheels	18" 7-spoke aluminum machined finish (Standard)
	18" 7-spoke chromed aluminum (Available)
	22" 7-spoke chromed aluminum (Included and only available on Ultra Luxury Collection)**
	22" multi-spoke chromed aluminum (Standard and only available on Platinum)**
Towing	
Towing Capacity	7,600 lbs. (RWD) [¥]
	7,800 lbs. (AWD) [¥]
Payload	1,493 lbs. (RWD) ^{¥¥}
	1,457 lbs. (AWD) ^{¥¥}

 $^{^{\}ensuremath{\mathsf{YY}}}$ Maximum payload capacity includes weight of driver, passengers, optional equipment and cargo.



^{*}Requires available 22" front wheels.

 $[\]ensuremath{^{**}}\text{Use}$ only GM-approved wheel/tire combinations. See dealer for details.

Ymaximum trailer-weight ratings are calculated assuming a base vehicle, except for any option(s) necessary to achieve the rating, plus driver. The weight of other optional equipment, passengers and cargo will reduce the maximum trailer weight your vehicle can tow. See your Cadillac dealer for additional details.