

Home > Products > Passenger Cars > Hongqi Luxury Sedans > [Hongqi HQ3](#)[Print](#) [Email this page](#)[Overview](#)[Exterior](#)[Interior](#)[Specifications](#)[Equipment](#)[Features](#)

SPECIFICATIONS

THE TECHNICAL PARAMETERS OF HQ3

Technical Parameters	HQ430		HQ300
	Type for Succeed persons	Type For Grand	Type For Business
General Construction			
Overall Length(mm)	4965	4965	
Overall Width(mm)	1795	1795	
Overall Height(mm)	1485	1485	
Wheelbase(mm)	2850	2850	
Tread Front/Rear (mm)	1535/1535	1535/1535	
Turning Radius Min.(m)	5.2	5.2	
Luggage Compartment Capacity (VDA Type) (L)	430	430	430
Nominal Total Weights (kg)	1775	1730	1730
GR Clearance W/Axle (mm)	150	150	
Parameter of Wind Resistance	0.27	0.27	
Safe Level of Passivity	NCAP 5	NCAP 5	
Power Assy			
Marking of Engine	3UZ-FE	3GR-FE	
Engine Type	V8/DOHC/32V (VVT-i)	V6/DOHC/24V (DUAL-VVT-i)	
Engine Technics	ETCS-i, ACIS		
Engine Capacity(cc)	4292	2995	
Max Power and Rpm Max Power (Kw/rpm)	206/5600	170/6200	
Max Torque(Nm/rpm)	430/3400	300/4400	
Compression Ratio	10.5	10.5	
Oil	No Plumbum Gasoline Beyond 95 #	No Plumbum Gasoline Beyond 95 #	
Fuel Tank Capacity(L)	70	70	
EC(L/100km)	11.3	10.1	
EC90km/h(L/100km)	6.9	5.8	
0-100km/h ACCELERATED TIME (s)	7.3	8.7	
Max Speed(km/h)	250	235	
Transmission	A761E 6AT	A760E 6AT	
Drive Type	Engine Front Configuration and Rear Drive	Engine Front Configuration and Rear Drive	
Tyre and Chassis			
Tyre Size	215/55 R17	215/55 R17	
Spare Wheel Standard	Full Dimension	Full Dimension	
FR Suspension Type	Double Wishbone, Coil, Have Subframe (Member) , Have Bar, Stabilizer		
RR Suspension Type	Multilink, Coil, Have Subframe (Member), Have Bar, Stabilizer		
FR/RR Brake	Ventilated Disc Brake with Floating Caliper 1-Cylinder		
Power Control System	ABS, EBD, BA, TRC, VSC, HAC		

[BACK TO TOP ▲](#)