Home > Products > SUVs & Pickups > Sport Utility Vehicles(SUVs) > CA6480P6E

		🖴 Print 🛛 🖾 Email this page
Exterior	Interior	Specifications

SPECIFICATIONS

Model	CA6480P6E
Passenger Capacity	5-7
Weights and Capacities (kg)	
Load Capacity	
Front Axle Curb Weight	874
Rear Axle Curb Weight	621
Total Curb Weight	1,495
Front GAW (gross axle weight)	870
Rear GAW	1,450
GVW (gross vehicle weight)	2,320
Dimensions (mm)	
Overall	5,140×1,790×1,825/1,840/1,925/1,940
Pickup Bed (interior)	
Wheelbase	3,025
Axle Track (front/rear)	1,460/1,450
Spring Center to Center (front/rear)	780/1,335
Performance	
Max. Gradeability (%)	31
Top Speed (km/h)	135
Min. Turning Diameter (m)	12
Braking Distance (m) (from 60km/h at full load)	≤61.2
Min. Ground Clearance (mm)	185
Approach/Departure Angle (°) (front/rear)	27/23
Fuel Consumption (L/100km at 60km/h with full load)	9
Max. Exterior Noise Level (dBA)	77
Max. Operating Range (km)	400
Engine	
Model	JM491Q-ME/XG491Q-ME
Туре	4 Cylinder Inline, OHC, Multi-point Fuel Injection
Displacement (L)	2.237/2.237
Peak Power (kW) @ rpm	76 @ 4,200-4,600
Max.Torque (N.m) @ rpm	193 @ 2,000-2,600
Bore & Stroke (mm)	91×86
Compression Ratio	8.8:1
Emissions Rating	Euro-2
Fuel Capacity (L)	60
Clutch	Dry Single Plate, Diaphragm Type, Dampened
Gear-box	5 Speeds Forward / 1 Reverse, Overdrive in 5th, Synchronized

Steering system	Integral Power Steering, Gear Ratio 23.76 (Optional Power Steering)	
Propeller Shaft	Spicer type, 2 section with hanger bearing	
Cab	5 Door SUV	
Frame	Ladder Type, Channel Section Side Rail, Riveted Boxed Construction	
Rear Axle	Hypoid Single Reduction, Fabricated Axle Housing, Semi-floating, Ratio 4.55	
Front Suspension	Coil-spring Double Wishbone with Double Acting Telescopic Shoc Absorbers	
Rear Suspension	Leaf Spring Suspension with Double Acting Telescopic Shock Absorbers	
Tires	215/75R15	
Brake System	Dual Circuit Hydraulic System with Vacuum Assist	
Body		
Electrical System	12V, Negative Ground	

вяск то тор 🔺